

Date Generated: 02.05.24

T32 Product Data Sheet

Material Details

Grade:	T32. (Type: Glass Fibre - SRBG (Not manufactured by The Attwater Group))
Description:	Silicone Glass. (Not manufactured by The Attwater Group)
Comments:	A high quality silicone glass tube manufactured from a medium E type glass fabric with silicone resin. T32 exhibits excellent electrical properties coupled with low water absorption, good insulation resistance and is suitable for use both at high temperatures and in high frequency applications.
Specifications:	BSEN61212-3-1 SIGC21 (Which supersedes BS6128 SIGC81). The closest NEMA equivalent to this specification is G7.
Body Colour:	White
Standard Finish:	Ground (unless otherwise stated)
Size:	1220mm trimmed (max) Thickness Range: Min ID 10.0mm, Min wall 1.0mm(Ground) 2.0mm(as produced). †

General Properties

Property	Unit of measure	Typical Value
Density	g/cm ³	1.9
Water Absorption	mg	1
Flammability Category†	-	FV0

‡ Where relevant, the flammability test method is used solely to control and monitor consistency of production. Under no conditions should the results be considered in relation to fire hazards under actual conditions of use.

Electrical Properties

Property	Unit of measure	Typical Value
IR (24hrs Water Immersed)	G □	3000
IR (Dry)	G □	3000
Radial Electric Strength	MV/m	8

Mechanical Properties

Property	Unit of measure	Typical Value
Cohesion	-	100
Axial Compressive	-	40

Thermal Properties

Property	Unit of measure	Typical Value
Thermal Rating Continuous	°C	200

Notes

- Datasheet Issue No. 1

Disclaimer: The above values are based upon routine test data and do not form the basis of a supply contract. These products may be used in a diverse range of applications and whilst every effort is made to ensure the information in this data sheet is accurate, it must be stressed that it is the user's responsibility to ensure suitability for the intended end use.

Source: <https://www.attwater.com/products/t32/>