

**Date Generated: Monday 23rd of February 2026**

## **T10 \* Product Data Sheet**

# **BSEN61212 PFCC21 T10 Electrical Grade Phenolic Cotton Tube SRBP & SRBF**

### **Material Details**

<b>Grade:</b>	T10 *
<b>Description:</b>	Phenolic Cotton. Electrical Grade
<b>Comments:</b>	A high quality Phenolic cotton tube manufactured from fine weave cloth and phenolic resin.  T10 tube exhibits excellent electrical and mechanical properties and may be machined to a fine finish.
	* Not manufactured by The Attwater Group
<b>Specifications:</b>	BSEN61212 PFCC21 (Which supersedes BS6128 PFCC81). The closest NEMA equivalent to this specification is LE
<b>Body Colour:</b>	Light brown
<b>Finish:</b>	Ground (unless otherwise stated)
<b>Size:</b>	1220mm trimmed (max)  Thickness Range: Min ID 8.0mm, Min wall 1.0mm(Ground) 2.0mm(as produced).

### **General Properties**

<b>Property</b>	<b>Unit of measure</b>	<b>Typical Value</b>
Density	g/cm3	1.35

Property	Unit of measure	Typical Value
Water Absorption	mg	2.5

⌘ Where relevant, the flammability test method is used solely to control and monitor consistency of production. Under no conditions should the results be considered in relation to fire hazards under actual conditions of use.

## Electrical Properties

Property	Unit of measure	Typical Value
IR (24hrs Water Immersed)	G Ω	0.09
IR (Dry)	G Ω	0.09
Radial Electric Strength	MV/m	3.5

## Mechanical Properties

Property	Unit of measure	Typical Value
Cohesion	--	180
Axial Compressive	--	200

## Thermal Properties

Property	Unit of measure	Typical Value
Thermal Rating Continuous	°C	120

Disclaimer: The above values are based upon routine test data and do not form the basis of a supply contract. These products may be used in a diverse range of applications and whilst every effort is made to ensure the information in this data sheet is accurate, it must be stressed that it is the user's responsibility to ensure suitability for the intended end use.

Source: <https://www.attwater.com/products/t10/>